

## **Section 1: Identification**

1.1. Product identifier

Product form : Substance

Product Identifier(s) : Wingtack® EXTRA

Wingtack® EXTRA Flake Wingtack® EXTRA Pastille Wingtack® EXTRA Molten

WT EXTRA

CAS No : 62258-49-5

1.2. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Additive for paints, coatings, inks, adhesives

Rubbers

1.3. Details of the supplier of the safety data sheet

Total Petrochemicals & Refining USA, Inc. Cray Valley Division PO Box 674411 Houston,TX 77267-4411

For non-emergency product information: Phone: 713-483-5000 or 1-877-871-2709 Email: product.stewardship@total.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (Toll Free USA & Canada) / 703-527-3887 (Multiple languages)

Total Petrochemicals & Refining USA, Inc.: 1-800-322-3462 (Language: English only)

### **Section 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# Classification (GHS-US)

Combustible Dust

# 2.2. Label elements

# **GHS-US labeling**

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : May form combustible dust concentrations in air

Precautionary statements (GHS-US) : Precautionary statement not required.

### 2.3. Hazards not otherwise classified

No additional information available

# 2.4. Unknown acute toxicity (GHS-US)

Not applicable

### 2.5. Additional information

Based on conditions common to industrial workplace use of this product

: Contact with skin or eyes with hot material may cause serious thermal burns to skin or eyes. Vapors formed when material is processed at high temperatures may be irritating to the eyes and upper respiratory tract.

Based on professional judgment, inconclusive

testing, or sensitive individuals

: Dust from this product may cause respiratory irritation

Repeated or prolonged contact may cause slight irritation to the skin

# Section 3: Composition/information on ingredients

# 3.1. Substance

Chemical name : Benzene, (1-methylethenyl)-, polymer with 2-methyl-2-butene and 1,3-pentadiene

 Date of issue: 09/18/2014
 EN (English US)
 Page 1

# Safety Data Sheet

CAS No : 62258-49-5

Generic name : Aromatically-modified C5 Petroleum Hydrocarbon Resin

### 3.2. Mixture

Not applicable

# Section 4: First aid measures

# 4.1. Description of first aid measures

First-aid measures after inhalation
First-aid measures after skin contact

First-aid measures after eye contact

: Remove to fresh air and keep at rest in a position comfortable for breathing.

: Wash with plenty of soap and water. If irritation persists, consult a doctor. Heated Material: For serious burns from heated material, get medical attention. In case of skin contact, immediately

immerse in or flush with clean, cold water. Do not attempt to remove adhered material from skin.

: Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking, tears

or redness persist.

First-aid measures after ingestion : Rinse mouth out with water. If necessary seek medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **Section 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Foam. Dry chemical.

### 5.2. Special hazards arising from the chemical

Fire hazard

: May form combustible dust concentrations in air. Vapors generated from

overheating/melting/decomposition may be flammable and may cause fire/explosion if source of

ignition is present.

Explosion hazard

: Potential dust explosion hazard. When dust becomes airborne and is exposed to an ignition source, sufficient combustible/flammable dust may exist to burn in the open or explode if confined. The minimum explosive dust cloud for Wingtack dust was measured to be 0.12 oz/ft3.

Hazardous decomposition products in case of

tire

: Carbon oxides (CO, CO2). Toxic fumes.

### 5.3. Advice for firefighters

Firefighting instructions

: Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Avoid raising powdered materials into airborne dust, creating an explosion hazard. Apply aqueous extinguishing media carefully to prevent frothing/steam explosion. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting

Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.

### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Emergency procedures for non-emergency personnel

: Remove ignition sources. Ensure adequate ventilation. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures for emergency responders

: No additional requirement.

### 6.2. Methods and material for containment and cleaning up

For containment : Sweep up or vacuum up the product.

Methods for cleaning up : Dispose of materials or solid residues at an authorized site.

## 6.3. Reference to other sections

See section 8. Exposure controls/personal protection.

Date of issue: 09/18/2014 EN (English US) 2/6

# Safety Data Sheet

# Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling

Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with heated product to prevent burns. Prevent the build-up of electrostatic charge. Use only nonsparking tools. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. The plastic packaging film used to secure bags of material on pallets can also develop static electricity -- remove packaging film in an area free from ignitable vapors/dust. Refer to the latest edition of the National Fire Protection Association (NFPA) 654 publication, "Standard for the Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries", for complete discussion on dust explosion prevention and control measures. This material may be shipped as a viscous, molten product at elevated temperatures (approximately 204 °C), but below its flashpoint, to facilitate transfer to storage containers or

processing vessels. If frozen, thaw and mix thoroughly before use.

Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Electrical equipment should conform to the National Electric Code.

Keep container tightly closed. Store in a dry, cool area. Flaked forms may degrade by gradual Storage conditions

oxidation. Protect from freezing.

Maximum storage period : 12 months Storage temperature : < 40 °C

### Section 8: Exposure controls/personal protection

#### 8.1. **Occupational Exposure Limits**

Wingtack® EXTRA (62258-49-5)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable dust) 3 mg/m³ (respirable dust)
USA ACGIH	Remark (ACGIH)	Particulates, not otherwise classified
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable dust)
USA OSHA	Remark (US OSHA)	Particulates, not otherwise classified

#### 8.2. **Exposure controls**

Appropriate engineering controls : Ensure good ventilation of the work station. Protective gloves made of rubber or PVC. Hand protection

Eye protection Safety glasses.

Skin and body protection : Wear fire/flame resistant/retardant clothing. Wear suitable protective clothing.

: In case of inadequate ventilation wear respiratory protection. Respiratory protection

### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Solid

: Flakes. Pastilles. Appearance Pale yellow. Color Odor : Mild.

Odor threshold

No data available pН Not applicable Relative evaporation rate (butyl acetate=1) : No data available Melting point No data available Freezing point : No data available Boiling point : No data available Flash point ~ 225 °C (PMCC) Auto-ignition temperature : No data available Decomposition temperature : No data available : No data available Flammability (solid, gas)

Vapor pressure : 6 mm Hg @204°C/400°F

Relative vapor density at 20 °C : No data available

Relative density : 0.96

Date of issue: 09/18/2014 EN (English US) 3/6

# Safety Data Sheet

Solubility : Water: Insoluble : No data available Log Kow Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive limits : No data available

9.2. Other information

Explosive properties : Explosion Index, Kst (bar. m/s) : 200 - 315\*.

Minimum ignition energy : < 3 mJSoftening point ~ 97 °C

Additional information : Data denoted with an asterisk is from a representative product or class of products

### Section 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under use and storage conditions as recommended in section 7.

#### 10.3. Possibility of hazardous reactions

Dust may form explosive mixture in air.

#### 10.4. Conditions to avoid

Avoid the build-up of electrostatic charge. High temperature. Avoid dust formation. Direct sunlight.

#### 10.5. Incompatible materials

Oxidizing agents. Strong acids.

### Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **Section 11: Toxicological information**

#### 11.1. Information on toxicological effects

Likely routes of exposure : Ingestion. Skin and eye contact.

Acute toxicity : Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation : Not classified

Based on available data, the classification criteria are not met

Practically non-irritating

(rabbit)

Serious eye damage/irritation : Not classified

Based on available data, the classification criteria are not met

Respiratory or skin sensitization : Not classified

Based on available data, the classification criteria are not met

Does not cause cutaneous sensitization for guinea-pigs

Germ cell mutagenicity : Not classified

Lack of data

Carcinogenicity : Not classified

Lack of data

: Not classified Reproductive toxicity

Lack of data

Specific target organ toxicity (single exposure) : Not classified

Lack of data

Specific target organ toxicity (repeated : Not classified

exposure) Lack of data

Date of issue: 09/18/2014 EN (English US)

# Safety Data Sheet

Aspiration hazard

: Not classified

Not applicable

Potential Adverse human health effects and

symptoms

: Product may cause mild skin irritation. Dust from this product may cause eye irritation. Dust from this product may cause respiratory irritation.

# Section 12: Ecological information

#### 12.1. **Toxicity**

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

### Mobility in soil

No additional information available

#### 125 Other adverse effects

No additional information available

# **Section 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods

: Transfer to a safe disposal area in accordance with federal, state, and local regulations.

## Section 14: Transport information

### US Transport (DOT) for Bulk Shipments (Non-Bulk Shipments May Differ)

Not a DOT controlled material

If shipped as a liquid material at a temperature above 100 °C, this product should be classified for US DOT as: UN 3257, Elevated temperature liquid, n.o.s. (petroleum hydrocarbon resin), 9, PG III

### Transport by sea (IMDG)

Not an IMDG controlled material

### Air transport (IATA)

Not an IATA controlled material

# **Section 15: Regulatory information**

## 15.1. US Federal regulations

# Wingtack® EXTRA

**TSCA** 

All components of this product are listed or exempted from listing on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### **SARA 313**

This product contains no chemicals in excess of the applicable de minimis concentration that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (Table 372.65).

SARA Section 311/312 Hazard Classes Fire hazard

Export Control Classification Number (ECCN): EAR99 (No License Required)

# 15.2. International regulations

### **CANADA**

No additional information available

### National inventories

# Benzene, (1-methylethenyl)-, polymer with 2-methyl-2-butene and 1,3-pentadiene (62258-49-5)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Substances List) inventory

Listed on the China Inventory of Existing Chemical Substances (IECSC)

Listed on the Korean ECL (Existing Chemical List) inventory.

Date of issue: 09/18/2014 5/6 EN (English US)

# Safety Data Sheet

Listed on New Zealand - Inventory of Chemicals (NZIoC)

Listed on the Philippines Inventory of Chemicals and Chemical Substances (PICCS)


## 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity, not limited to any that may be listed below.

### **Section 16: Other information**

### NFPA (National Fire Protection Association)

NFPA health hazard : 1 NFPA fire hazard : 1 : 0 NFPA reactivity



**HMIS III Rating** 

Health : 1 Flammability 1 Physical Hazard : 0

Personal Protection : See section 8 of SDS

US OSHA LABEL as specified under 29 CFR §1910.1200 (f)

# Wingtack® EXTRA

Wingtack® EXTRA Flake Wingtack® EXTRA Pastille Wingtack® EXTRA Molten WT EXTRA

Total Petrochemicals & Refining USA, Inc., Cray Valley Division PO Box 674411

Houston, TX 77267-4411 USA Tel. 713-483-5000 or 1-877-871-2709

# Warning

# May form combustible dust concentrations in air

Precautionary statement not required.

Version: 2.0

Date of issue: September 18, 2014

MSDS ID: WINGTACK EXTRA SDS REFERENCE NUMBER: 0239M

SDS Template - TOTAL SDS US (GHS HazCom 2012) TPRI Version 2.06L

The information contained in this Safety Data Sheet (SDS) is believed by Total Petrochemicals & Refining USA, Inc. (TPRI) to be accurate on the date issued. However, materials may present unknown hazards and should be used with caution. Final determination of suitability and use of any material is the sole responsibility of the user. Neither TPRI nor any of its subsidiaries or affiliated companies assumes any liability whatsoever for the accuracy or completeness of the information contained herein or reliance thereto. If the material is repackaged, the user is responsible and must ensure that proper health, safety and other necessary information is included with the material and/or on the container. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING THE MATERIALS OR THE INFORMATION CONTAINED IN THIS SDS. ALTERATION OF THIS DOCUMENT IS STRICTLY PROHIBITED.

Date of issue: 09/18/2014 EN (English US) 6/6