



# Wingtack® RWT7850

## Safety Data Sheet

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

### Section 1: Identification

#### 1.1. Product identifier

Product form : Substance  
Product Identifier(s) : Wingtack® RWT7850  
Wingtack® RWT7850 Flake  
Wingtack® RWT7850 Pastille  
Wingtack® RWT7850 OS  
WT RWT7850  
CAS-No. : 26813-14-9

#### 1.2. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Additive for paints, coatings, inks, adhesives  
Rubbers

#### 1.3. Details of the supplier of the safety data sheet

Resin Solutions, LLC  
665 Stockton Drive, Suite 100  
Exton, PA 19341

For non-emergency product information:  
Phone: +1-484-284-8998  
Email: [product.stewardship@resinsolutions.com](mailto:product.stewardship@resinsolutions.com)

#### 1.4. Emergency telephone number

Emergency number : +1-484-284-8989

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Combustible Dust

#### 2.2. Label elements

##### GHS US labeling

Signal word (GHS US) : Warning  
Hazard statements (GHS-US) : **If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air**  
Precautionary statements (GHS-US) : Precautionary statements not required. Consult the SDS for additional safety information.

#### 2.3. Hazards not otherwise classified

Other hazards which do not result in classification : Contact with hot material - prevent serious burns  
Dust or particulates may cause mild respiratory tract and eye irritation  
May cause mild skin irritation.  
Combustible Dust  
Dust may form an explosive mixture with air, ignited by sparks or sources of ignition.  
Flowing product can create electrical charge, resulting sparks may ignite dust or cause an explosion in some concentration ranges.

#### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

#### 2.5. Additional information

Based on conditions common to industrial workplace use of this product : Contact with skin or eyes with hot material may cause serious thermal burns.  
Vapors formed when material is processed at high temperatures may be irritating to the eyes and upper respiratory tract.

Based on professional judgment, inconclusive testing, or sensitive individuals : Dust or particulates may cause mild respiratory tract and eye irritation.  
Repeated or prolonged contact may cause slight irritation to the skin

# Wingtack® RWT7850

## Safety Data Sheet

### Section 3: Composition/Information on ingredients

#### 3.1. Substance

Substance type	: Polymer
Name	: Wingtack® RWT7850
CAS-No.	: 26813-14-9
Chemical name	: 1,3-Pentadiene, polymer with 2-methyl-2-butene
Generic name	: Aliphatic C5 Petroleum Hydrocarbon Resin

#### 3.2. Mixture

Not applicable

### Section 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Wash with plenty of soap and water. If irritation persists, consult a doctor. Heated Material: For serious burns from heated material, get medical attention. In case of skin contact, immediately immerse in or flush with clean, cold water. Do not attempt to remove adhered material from skin.
First-aid measures after eye contact	: Obtain medical attention if pain, blinking, tears or redness persist. Immediately flush eyes thoroughly with water for at least 15 minutes. Heated Material: For serious burns from heated material, get medical attention. In case of contact with the eyes : Rinse immediately with plenty of water for 15 minutes.
First-aid measures after ingestion	: Rinse mouth out with water. If necessary seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Dust or particulates may cause mild respiratory tract and eye irritation.
Symptoms/effects after skin contact	: Contact with hot material - prevent serious burns. May cause mild skin irritation.
Symptoms/effects after eye contact	: Contact with hot material - prevent serious burns.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### Section 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray or fog. Carbon dioxide. Foam. Dry chemical. Dry powder. Sand.
Unsuitable extinguishing media	: Use of heavy stream of water may spread fire.

#### 5.2. Special hazards arising from the chemical

Fire hazard	: Vapors generated from overheating/melting/decomposition may be flammable and may cause fire/explosion if source of ignition is present.
Explosion hazard	: Potential dust explosion hazard. When dust becomes airborne and is exposed to an ignition source, sufficient combustible/flammable dust may exist to burn in the open or explode if confined. The minimum explosive dust cloud for Wingtack dust was measured to be 0.12 oz/ft <sup>3</sup> .
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO <sub>2</sub> ). Toxic fumes.

#### 5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Avoid raising powdered materials into airborne dust, creating an explosion hazard. Apply aqueous extinguishing media carefully to prevent frothing/steam explosion. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Emergency procedures for non-emergency personnel	: Material creates a slipping hazard on hard surfaces. Clean up spills from walking surfaces immediately. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures for emergency responders	: No additional requirement.

#### 6.2. Methods and material for containment and cleaning up

For containment	: Sweep up or vacuum up the product.
Methods for cleaning up	: Dispose of materials or solid residues at an authorized site. Notify authorities if product enters sewers or public waters.

# Wingtack® RWT7850

## Safety Data Sheet

### 6.3. Reference to other sections

See section 8. Exposure controls/personal protection.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Minimize generation of dust. Avoid raising dust clouds. Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with heated product to prevent burns. Prevent the build-up of electrostatic charge. Use only non-sparking tools. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. The plastic packaging film used to secure bags of material on pallets can also develop static electricity -- remove packaging film in an area free from ignitable vapors/dust. Refer to the latest edition of the National Fire Protection Association (NFPA) 654 publication, "Standard for the Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries", and "Combustible Dust in Industry: Preventing and Mitigating the Effects of Fire and Explosions" (OSHA SHIB, July 31, 2005, updated Nov. 12, 2014, <https://www.osha.gov/dts/shib/shib073105.html>) for a complete discussion on dust explosion prevention and control measures. This material may be shipped as a viscous, molten product at elevated temperatures (up to 204 °C) to facilitate transfer to storage containers or processing vessels. If frozen, allow to warm to room temperature before adding to a process to prevent water condensation from entering the process.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Electrical equipment should conform to the National Electric Code.
- Storage conditions : Keep container tightly closed. Store in a dry, cool area. Flaked forms may degrade by gradual oxidation. Keep away from sources of ignition.
- Incompatible materials : Strong acids.
- Storage temperature : < 35 °C

## Section 8: Exposure controls/personal protection

### 8.1. Occupational Exposure Limits

The following constituents are the only constituents of the product which have a PEL, TLV, or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Wingtack® RWT7850 (26813-14-9)		
USA ACGIH	ACGIH OEL TWA	10 mg/m <sup>3</sup> (inhalable dust) 3 mg/m <sup>3</sup> (respirable dust)
USA ACGIH	Remark (ACGIH)	Particulates, not otherwise classified
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
USA OSHA	Remark (OSHA)	Particulates, not otherwise classified

### 8.2. Exposure controls

- Appropriate engineering controls : Provide readily accessible eye wash stations and safety showers. Ensure good ventilation of the work station.
- Hand protection : Protective gloves made of rubber or PVC.
- Eye protection : Safety glasses with side shields.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : Flakes. Pastilles.
- Color : Pale yellow.
- Odor : Mild.
- Odor threshold : No data available
- pH : Not applicable
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : Not applicable
- Initial boiling point and boiling range : Not applicable
- Flash point : ~ 225 °C (PMCC)

# Wingtack® RWT7850

## Safety Data Sheet

Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability	: No data available
Vapor pressure	: 8 mm Hg (204°C/400°F)
Relative vapor density at 20°C	: Not applicable
Relative density	: 0.95
Solubility	: Water: Insoluble
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable
Explosion limits	: No data available

### 9.2. Other information

Explosive properties	: Explosion Index, Kst (bar. m/s) : 200 - 315* Max. Explosive Pressure (Pmax), bar : 8.8* Dust may form explosive mixture in air.
Minimum ignition energy	: 1 – 3 mJ *
Softening point	: 102 °C
Additional information	: Data denoted with an asterisk is from a representative product or class of products

## Section 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under use and storage conditions as recommended in section 7.

### 10.3. Possibility of hazardous reactions

Dust may form explosive mixture in air.

### 10.4. Conditions to avoid

Avoid the build-up of electrostatic charge. High temperature. Avoid dust formation. Direct sunlight. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong acids.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Likely routes of exposure	: Ingestion. Skin and eye contact.
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified Practically non-irritating (rabbit)
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified Does not cause cutaneous sensitization for guinea-pigs
Germ cell mutagenicity	: Not classified

# Wingtack® RWT7850

## Safety Data Sheet

Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified Not applicable
Potential Adverse human health effects and symptoms	: Dust or particulates may cause mild respiratory tract and eye irritation.

### Section 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Do not allow product to spread into the environment.

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Transfer to a safe disposal area in accordance with federal, state, and local regulations.  
Product/Packaging disposal recommendations : Dispose of contents and container in accordance with all local, regional, national and international regulations.

### Section 14: Transport information

#### US Transport (DOT) for Bulk Shipments (Non-Bulk Shipments May Differ)

Not regulated by US DOT

If shipped as a liquid material at a temperature above 100 °C, this product should be classified for US DOT as:  
UN 3257, Elevated temperature liquid, n.o.s. (petroleum hydrocarbon resin), 9, PG III

#### Transport by sea (IMDG)

Not regulated by IMDG

#### Air transport (IATA)

Not regulated by IATA

### Section 15: Regulatory information

#### 15.1. US Federal regulations

##### EPA TSCA Status

All components of this product are listed or exempt from listing on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) Active inventory. This product has no special requirements under TSCA, such as significant new use rules (SNUR), consent orders, test rules, or sections 4, 5, 6, 8(a), 8(d), 12(b) requirements.

##### SARA Section 313 Supplier Notification

This product contains no toxic chemicals in excess of the applicable de minimis concentration that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SARA Section 311/312 Hazard Classes Physical hazard - Combustible dust

# Wingtack® RWT7850

## Safety Data Sheet

Export Control Classification Number (ECCN): EAR99 (No License Required)

### 15.2. International regulations

#### CANADA

Wingtack® RWT7850 (26813-14-9)

WHMIS Classification

This product is not regulated according to WHMIS 2015 classification criteria

#### National inventories

Wingtack® RWT7850 (26813-14-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on or exempt from listing on the Canadian DSL (Domestic Substances List)

Listed on or exempt from listing on the AICS (Australian Inventory of Chemical Substances)

Listed on or exempt from listing on the Philippines Inventory of Chemicals and Chemical Substances (PICCS)

Listed on or exempt from listing on the Korean ECL (Existing Chemicals List)

Listed on or exempt from listing on the China Inventory of Existing Chemical Substances (IECSC)

Listed on or exempt from listing on NZIoC (New Zealand Inventory of Chemicals)

Listed on or exempt from listing on the TCSI (Taiwan Chemical Substance Inventory)

Listed on the NCI (Vietnam - National Chemical Inventory)

ENCS (Japanese Existing & New Chemical Substances inventory)

All components are listed or exempted

ISHL (Japan Industrial Safety and Health Law Substances)

All components are listed or exempted

### 15.3. US State regulations

California Proposition 65 - To the best of our knowledge, there are no Proposition 65 chemicals present in this product at levels that would require warning under the California Safe Drinking Water and Toxic Enforcement Act.

## Section 16: Other information

Other information

: Unless agreed to in a separate written agreement with the Customer, Resin Solutions, LLC makes no representations and disclaims all warranties, express or implied, with respect to biocompatibility and/or the suitability of this product for medical device applications including : (i) implantable devices intended for human or animal body, (ii) devices intended to be used in contact with internal body fluids, and (iii) devices intended to be used in contact with internal body tissues. If the Customer intends to use this product for any such application, it must first contact Resin Solutions, LLC and establish agreed terms and conditions for such use.

### NFPA (National Fire Protection Association)

NFPA health hazard


: 1

NFPA fire hazard

: 1

NFPA reactivity

: 0



### Hazard System Rating

Health

: 1

Flammability

: 1

Physical Hazard

: 0

Personal protection

: See section 8 of SDS

US OSHA LABEL as specified under 29 CFR §1910.1200 (f). The label shown may include supplemental information in addition to required elements.

**Wingtack® RWT7850**

Resin Solutions, LLC  
665 Stockton Drive, Suite 100  
Exton, PA 19341 USA  
Tel. +1-484-284-8989

### Warning

**If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air**

Precautionary statements not required. Consult the SDS for additional safety information.

US SDS Version: 3.1

Issue date: October 11, 2023

SDS ID: WINGTACK\_RWT7850

SDS ID: WINGTACK\_RWT7850

Language: EN (English US)

US SDS Version: 3.1

Issue date: 10/11/2023

Page 6/7

# Wingtack® RWT7850

## Safety Data Sheet

---

SDS REFERENCE NUMBER: 0248M

SDS Template - Resin Solutions LLC US Version 1.0

*The information contained in this Safety Data Sheet (SDS) is believed by Resin Solutions, LLC to be accurate on the date issued. However, materials may present unknown hazards and should be used with caution. Final determination of suitability and use of any material is the sole responsibility of the user. Neither Resin Solutions, LLC nor any of its subsidiaries or affiliated companies assumes any liability whatsoever for the accuracy or completeness of the information contained herein or reliance thereto. If the material is repackaged, the user is responsible and must ensure that proper health, safety and other necessary information is included with the material and/or on the container. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING THE MATERIALS OR THE INFORMATION CONTAINED IN THIS SDS. ALTERATION OF THIS DOCUMENT IS STRICTLY PROHIBITED.*