

Section 1: Identification**1.1. Product identifier**

Product form : Substance
Product Identifier(s) : Wingtack® RWT7850
Wingtack® RWT7850 Flake
Wingtack® RWT7850 Pastille
WT RWT7850
CAS-No. : 26813-14-9

1.2. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Additive for paints, coatings, inks, adhesives
Rubbers

1.3. Details of the supplier of the safety data sheet

Total Petrochemicals & Refining USA, Inc.
Cray Valley Division
PO Box 674411
Houston, TX 77267-4411

For non-emergency product information:
Phone: 713-483-5000 or 1-877-871-2729
Email: product.stewardship@total.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (Toll Free USA & Canada) / 703-527-3887 (Multiple languages)
Total Petrochemicals & Refining USA, Inc.: 1-800-322-3462 (Language: English only)

Section 2: Hazards identification**2.1. Classification of the substance or mixture****Classification (GHS-US)**

Combustible Dust

2.2. Label elements**GHS-US labeling**

Signal word (GHS-US) : **Warning**
Hazard statements (GHS-US) : **If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air**
Precautionary statements (GHS-US) : Precautionary statements not required. Consult the SDS for additional safety information.

2.3. Hazards not otherwise classified

Other hazards not contributing to the classification : Product can accumulate electrostatic charges that may cause fire by electrical discharges.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

2.5. Additional information

Based on conditions common to industrial workplace use of this product : Contact with skin or eyes with hot material may cause serious thermal burns.
Vapors formed when material is processed at high temperatures may be irritating to the eyes and upper respiratory tract.
Based on professional judgment, inconclusive testing, or sensitive individuals : Dust or particulates may cause mild respiratory tract and eye irritation.
Repeated or prolonged contact may cause slight irritation to the skin.

Section 3: Composition/Information on ingredients**3.1. Substance**

Chemical name : 1,3-Pentadiene, polymer with 2-methyl-2-butene
CAS-No. : 26813-14-9

Date of issue: 10/10/2018

EN (English US)

Page 1

Wingtack® RWT7850

Safety Data Sheet

Generic name : Aliphatic C5 Petroleum Hydrocarbon Resin

3.2. Mixture

Not applicable

Section 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Wash with plenty of soap and water. If irritation persists, consult a doctor. Heated Material: For serious burns from heated material, get medical attention. In case of skin contact, immediately immerse in or flush with clean, cold water. Do not attempt to remove adhered material from skin.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Obtain medical attention if pain, blinking, tears or redness persist.

First-aid measures after ingestion : Rinse mouth out with water. If necessary seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray or fog. Carbon dioxide. Foam. Dry chemical. Dry powder. Sand.

Unsuitable extinguishing media : Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the chemical

Fire hazard : Vapors generated from overheating/melting/decomposition may be flammable and may cause fire/explosion if source of ignition is present.

Explosion hazard : Potential dust explosion hazard. When dust becomes airborne and is exposed to an ignition source, sufficient combustible/flammable dust may exist to burn in the open or explode if confined. The minimum explosive dust cloud for Wingtack dust was measured to be 0.12 oz/ft3.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO2). Toxic fumes.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Avoid raising powdered materials into airborne dust, creating an explosion hazard. Apply aqueous extinguishing media carefully to prevent frothing/steam explosion. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Emergency procedures for non-emergency personnel : Material creates a slipping hazard on hard surfaces. Clean up spills from walking surfaces immediately.

Emergency procedures for emergency responders : No additional requirement.

6.2. Methods and material for containment and cleaning up

For containment : Sweep up or vacuum up the product.

Methods for cleaning up : Dispose of materials or solid residues at an authorized site. Notify authorities if product enters sewers or public waters.

6.3. Reference to other sections

See section 8. Exposure controls/personal protection.

Wingtack® RWT7850

Safety Data Sheet

Section 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Minimize generation of dust. Avoid raising dust clouds. Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with heated product to prevent burns. Prevent the build-up of electrostatic charge. Use only non-sparking tools. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. The plastic packaging film used to secure bags of material on pallets can also develop static electricity -- remove packaging film in an area free from ignitable vapors/dust. Refer to the latest edition of the National Fire Protection Association (NFPA) 654 publication, "Standard for the Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries", for complete discussion on dust explosion prevention and control measures. This material may be shipped as a viscous, molten product at elevated temperatures (approximately 204 °C), but below its flashpoint, to facilitate transfer to storage containers or processing vessels. If frozen, allow to warm to room temperature before adding to a process to prevent water condensation from entering the process.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Electrical equipment should conform to the National Electric Code.

Storage conditions : Keep container tightly closed. Store in a dry, cool area. Flaked forms may degrade by gradual oxidation.

Storage temperature : < 35 °C

Section 8: Exposure controls/personal protection

8.1. Occupational Exposure Limits

The following constituents are the only constituents of the product which have a PEL, TLV, or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Wingtack® RWT7850 (26813-14-9)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable dust) 3 mg/m ³ (respirable dust)
USA ACGIH	Remark (ACGIH)	Particulates, not otherwise classified
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	Remark (OSHA)	Particulates, not otherwise classified

8.2. Exposure controls

Appropriate engineering controls : Provide readily accessible eye wash stations and safety showers. Ensure good ventilation of the work station.

Hand protection : Protective gloves made of rubber or PVC.

Eye protection : Safety glasses.

Skin and body protection : Wear fire/flamm resistant/retardant clothing. Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Flakes. Pastilles.

Color : Pale yellow.

Odor : Mild.

Odor threshold : No data available

pH : Not applicable

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : ~ 225 °C (PMCC)

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Wingtack® RWT7850

Safety Data Sheet

Vapor pressure	: 8 mm Hg @204°C/400°F
Relative vapor density at 20 °C	: No data available
Relative density	: 0.95
Solubility	: Water: Insoluble
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available

9.2. Other information

Explosive properties	: Explosion Index, Kst (bar. m/s) : 200 - 315* Max. Explosive Pressure (Pmax), bar : 8.8*.
Minimum ignition energy	: < 3 mJ
Softening point	: 102 °C
Additional information	: Data denoted with an asterisk is from a representative product or class of products

Section 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under use and storage conditions as recommended in section 7.

10.3. Possibility of hazardous reactions

Dust may form explosive mixture in air.

10.4. Conditions to avoid

Avoid the build-up of electrostatic charge. High temperature. Avoid dust formation. Direct sunlight.

10.5. Incompatible materials

Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	: Ingestion. Skin and eye contact.
Acute toxicity	: Not classified Based on available data, the classification criteria are not met
Skin corrosion/irritation	: Not classified Based on available data, the classification criteria are not met Practically non-irritating (rabbit)
Serious eye damage/irritation	: Not classified Based on available data, the classification criteria are not met
Respiratory or skin sensitization	: Not classified Based on available data, the classification criteria are not met Does not cause cutaneous sensitization for guinea-pigs
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met

Wingtack® RWT7850

Safety Data Sheet

Specific target organ toxicity – single exposure	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity – repeated exposure	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified Not applicable

Section 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Transfer to a safe disposal area in accordance with federal, state, and local regulations.
Product/Packaging disposal recommendations	: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Section 14: Transport information

US Transport (DOT) for Bulk Shipments (Non-Bulk Shipments May Differ)

Not regulated by US DOT

If shipped as a liquid material at a temperature above 100 °C, this product should be classified for US DOT as: UN 3257, Elevated temperature liquid, n.o.s. (petroleum hydrocarbon resin), 9, PG III

Transport by sea (IMDG)

Not regulated by IMDG

Air transport (IATA)

Not regulated by IATA

Section 15: Regulatory information

15.1. US Federal regulations

EPA TSCA Status

All components of this product are listed or exempt from listing on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

SARA Section 313 Supplier Notification

This product contains no toxic chemicals in excess of the applicable de minimis concentration that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SARA Section 311/312 Hazard Classes	Fire hazard
Export Control Classification Number (ECCN):	EAR99 (No License Required)

Wingtack® RWT7850

Safety Data Sheet

15.2. International regulations

CANADA

Wingtack® RWT7850 (26813-14-9)

WHMIS Classification

This product is not regulated according to WHMIS 2015 classification criteria

National inventories

1,3-Pentadiene, polymer with 2-methyl-2-butene (26813-14-9)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the China Inventory of Existing Chemical Substances (IECSC)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the Philippines Inventory of Chemicals and Chemical Substances (PICCS)

ENCS (Japanese Existing & New Chemical Substances inventory)

All components are listed or exempted

ISHL (Japan Industrial Safety and Health Law Substances)

All components are listed or exempted

15.3. US State regulations

California Proposition 65 - To the best of our knowledge, there are no Proposition 65 chemicals present in this product at levels that would require warning under the California Safe Drinking Water and Toxic Enforcement Act.

Section 16: Other information

Other information

: Unless agreed to in a separate written agreement with the Customer, Total Petrochemicals & Refining USA, Inc. makes no representations and disclaims all warranties, express or implied, with respect to biocompatibility and/or the suitability of this product for medical device applications including : (i) implantable devices intended for human or animal body, (ii) devices intended to be used in contact with internal body fluids, and (iii) devices intended to be used in contact with internal body tissues. If the Customer intends to use this product for any such application, it must first contact Total Petrochemicals & Refining USA, Inc. and establish agreed terms and conditions for such use.

NFPA (National Fire Protection Association)

NFPA health hazard


: 1

NFPA fire hazard

: 1

NFPA reactivity

: 0



Hazard Rating

Health : 1

Flammability : 1

Physical Hazard : 0

Personal protection : See section 8 of SDS

US OSHA LABEL as specified under 29 CFR §1910.1200 (f)

Wingtack® RWT7850

Total Petrochemicals & Refining USA, Inc., Cray Valley Division
PO Box 674411
Houston, TX 77267-4411 USA
Tel. 713-483-5000 or 1-877-871-2729

Warning

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air

Precautionary statements not required. Consult the SDS for additional safety information.

US SDS Version : 2.8

Date of issue : October 10, 2018

MSDS ID: WINGTACK_RWT7850
SDS REFERENCE NUMBER: 0248M

SDS Template - TOTAL SDS US (GHS HazCom 2012) TPRI Version 5.05

Date of issue: 10/10/2018

EN (English US)

6/7

Wingtack® RWT7850

Safety Data Sheet

The information contained in this Safety Data Sheet (SDS) is believed by Total Petrochemicals & Refining USA, Inc. (TPRI) to be accurate on the date issued. However, materials may present unknown hazards and should be used with caution. Final determination of suitability and use of any material is the sole responsibility of the user. Neither TPRI nor any of its subsidiaries or affiliated companies assumes any liability whatsoever for the accuracy or completeness of the information contained herein or reliance thereto. If the material is repackaged, the user is responsible and must ensure that proper health, safety and other necessary information is included with the material and/or on the container. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING THE MATERIALS OR THE INFORMATION CONTAINED IN THIS SDS. ALTERATION OF THIS DOCUMENT IS STRICTLY PROHIBITED.