

Section 1: Identification

1.1. Product identifier

Product form : Mixture
Product Identifier(s) : Dymalink® 634
Dymalink® 634 ABC123, where ABC123 can be any combination of letters and/or numbers other than EPM or EPMR

1.2. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Activator
Adhesion promoter
Rubbers

1.3. Details of the supplier of the safety data sheet

Resin Solutions, LLC
665 Stockton Drive, Suite 100
Exton, PA 19341

For non-emergency product information:
Phone: +1-484-284-8998
Email: product.stewardship@resinsolutions.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (Toll Free USA & Canada) / 703-527-3887 (Multiple languages)
Resin Solutions, LLC: +1-484-284-8989 (Language: English only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Combustible Dust
Acute toxicity (oral) Category 4
Serious eye damage/eye irritation Category 1
Skin sensitization, Category 1

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS-US) :

Harmful if swallowed
May cause an allergic skin reaction
Causes serious eye damage
May form combustible dust concentrations in air

Precautionary statements (GHS-US) :

Avoid breathing dust.
Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing must not be allowed out of the workplace.
Wear face protection, eye protection, protective gloves.
If swallowed: Call doctor, a POISON CENTER if you feel unwell.
If on skin: Wash with plenty of water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call doctor.
Specific treatment (see Section 4.1 of SDS or information on this label).
Rinse mouth.
If skin irritation or rash occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Dispose of contents and container in accordance with all local, regional, national and

Dymalink® 634

Safety Data Sheet

international regulations

2.3. Hazards not otherwise classified

Other hazards which do not result in classification

- : Combustible Dust
- Dust may form explosive mixture in air
- Dust from this product may cause respiratory irritation
- Thermal decomposition products are produced at elevated temperatures and these may be flammable
- May cause slight irritation to the skin.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

2.5. Additional information

Based on conditions common to industrial workplace use of this product

- : See section 7: Handling and Storage

Based on professional judgment, inconclusive testing, or sensitive individuals

- : Dust from this product may cause respiratory irritation.
- May cause mild skin irritation.

Section 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Where concentration of substances listed for this product are given in ranges, the exact percentage is being withheld as a trade secret.

Name	CAS-No.	% (Weight Percent)
Zinc dimethacrylate	13189-00-9	80 - 100
Alkylated Phenol	Trade secret	1-5

Section 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Gently wash with plenty of soap and water. If irritation persists, consult a doctor.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Dust from this product may cause respiratory irritation.
- Symptoms/effects after skin contact : May cause an allergic skin reaction. May cause mild skin irritation.
- Symptoms/effects after eye contact : Causes serious eye damage.
- Symptoms/effects after ingestion : Swallowing a small quantity of this material presents some health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Section 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog. Carbon dioxide. Foam. Dry chemical. Dry powder. Sand.
- Unsuitable extinguishing media : Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the chemical

- Fire hazard : Vapors generated from overheating/melting/decomposition may be flammable and may cause fire/explosion if source of ignition is present.
- Explosion hazard : Potential dust explosion hazard. When dust becomes airborne and is exposed to an ignition source, sufficient combustible/flammable dust may exist to burn in the open or explode if confined. Local exhaust and general room ventilation are both essential to prevent accumulation of flammable vapor or dust mixtures.
- Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂). Metallic oxides. Metallic peroxides. Toxic fumes.

5.3. Advice for firefighters

- Firefighting instructions : Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Avoid raising powdered materials into airborne dust, creating an explosion hazard. Apply aqueous extinguishing media carefully to prevent frothing/steam explosion. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Dymalink® 634

Safety Data Sheet

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Emergency procedures for non-emergency personnel : Ensure adequate ventilation. Avoid breathing dust. Avoid contact with skin, eyes and clothing. Remove ignition sources. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures for emergency responders : No additional requirement.

6.2. Methods and material for containment and cleaning up

For containment : Sweep up or vacuum up the product. Avoid creating or spreading dust.

Methods for cleaning up : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

See section 8. Exposure controls/personal protection.

Section 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all contact with skin, eyes, or clothing. Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with elevated temperature or molten product to prevent burns. Avoid raising powdered material due to explosion hazard. Prevent the build-up of electrostatic charge. Use only non-sparking tools. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Refer to the latest edition of the National Fire Protection Association (NFPA) 654 publication, "Standard for the Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries", and "Combustible Dust in Industry: Preventing and Mitigating the Effects of Fire and Explosions" (OSHA SHIB, July 31, 2005, updated Nov. 12, 2014, <https://www.osha.gov/dts/shib/shib073105.html>) for a complete discussion on dust explosion prevention and control measures. Although these publications discuss inerting as a method of protection against dust explosion, an inert gas atmosphere is not recommended during handling of this material because the inhibitor in this product requires oxygen to be effective.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Electrical equipment should conform to the National Electric Code.

Storage conditions : Keep container tightly closed in a cool, well-ventilated place. Store in a dry, cool area. Protect from moisture.

This material must be stored under the specified conditions. At elevated storage temperatures, the material may undergo self-reaction. In a low-oxygen, high-temperature environment, it may polymerize. In a normal-oxygen, high-temperature environment, it may oxidize. At temperatures at or above about 150°C (about 300°F), either self-reaction may accelerate rapidly. Both reactions generate heat and may result in fire.

Incompatible materials : Strong reducing agents. Strong oxidizing agents.

Storage temperature : 10 – 32 °C

Section 8: Exposure controls/personal protection

8.1. Occupational Exposure Limits

The following constituents are the only constituents of the product which have a PEL, TLV, or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Dymalink® 634		
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	Remark (OSHA)	Particulates, not otherwise classified
Zinc dimethacrylate (13189-00-9)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³ (inhalable dust) 3 mg/m ³ (respirable dust)
USA ACGIH	Remark (ACGIH)	Particulates, not otherwise classified

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Safety shower. Eye fountain.

Hand protection : Protective gloves. Do not use natural rubber gloves. Product used with solvents : wear thick (> 0.5 mm) nitrile gloves. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility, etc.) is noticed.

Dymalink® 634

Safety Data Sheet

Eye protection	: Chemical goggles or face shield.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Color	: White.
Odor	: Slightly acidic.
Odor threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: Not applicable
Initial boiling point and boiling range	: No data available
Flash point	: No data available
Auto-ignition temperature	: 377 °C
Decomposition temperature	: > 200 °C
Flammability	: No data available
Vapor pressure	: 0.00000784 Pa
Relative vapor density at 20°C	: Not applicable
Relative density	: 1.48
Solubility	: Water: Slightly soluble
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable
Explosion limits	: No data available

9.2. Other information

Explosive properties	: Explosion Index, Kst (bar. m/s) : 141 (estimate based on similar tested products) Max. Explosive Pressure (Pmax), bar : 7.4 (estimate based on similar tested products) Particle size: < 100 microns (approximately 100%), L50 = 13 microns.
Minimum ignition energy	: > 10 (10 – 25) mJ (estimate based on similar tested products)

Section 10: Stability and reactivity

10.1. Reactivity

Unstable (reactive) on depletion of inhibitor.

10.2. Chemical stability

Stable under use and storage conditions as recommended in section 7.

10.3. Possibility of hazardous reactions

This material must be stored under the specified conditions. At elevated storage temperatures, the material may undergo self-reaction. In a low-oxygen, high-temperature environment, it may polymerize. In a normal-oxygen, high-temperature environment, it may oxidize. At temperatures at or above about 150°C (about 300°F), either self-reaction may accelerate rapidly. Both reactions generate heat and may result in fire.

Normal use of this product in a high-temperature process under recommended conditions will not result in these hazardous reactions.

10.4. Conditions to avoid

Avoid the build-up of electrostatic charge. Avoid dust formation. High temperature. Direct sunlight. Sparks. Open flame. Conditions which remove all oxygen from the product (the inhibitor requires presence of oxygen to prevent autopolymerization). High humidity. This product is an anhydrous salt that will readily absorb moisture upon exposure to a humid atmosphere.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11: Toxicological information

11.1. Information on toxicological effects

Dymalink® 634

Safety Data Sheet

Likely routes of exposure : Inhalation. Ingestion. Skin and eye contact.

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Zinc dimethacrylate (13189-00-9)	
LD50 oral rat	500 mg/kg (OECD 423 method)
LC50 inhalation rat	> 5320 mg/m ³ (OECD 436 method)

Alkylated Phenol (Trade secret)	
LD50 oral rat	461 mg/kg body weight (OECD Guideline 401)(OECD 401 method)
LD50 dermal rabbit	> 4000 mg/kg body weight (Similar to OECD guideline 402)

Skin corrosion/irritation : Not classified
Practically non-irritating
(rabbit)

Serious eye damage/irritation : Causes serious eye damage.
(rabbit)

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified
Ames test : negative

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified
Not applicable

Section 12: Ecological information

12.1. Toxicity

Ecology - general : Do not allow product to spread into the environment.

Zinc dimethacrylate (13189-00-9)	
LC50 - Fish [1]	96.73 mg/l (OECD 203 method)
LC50 - Other aquatic organisms [1]	0.56 mg/l (OECD 201 method)
EC50 - Crustacea [1]	8.61 mg/l (OECD 202 method) Read-across (Analogy) 16039-53-5

Alkylated Phenol (Trade secret)	
LC50 - Fish [1]	1.346 mg/l QSAR estimate for phenol amines class, ECHA data
LC50 - Other aquatic organisms [1]	0.659 mg/l (daphnia) QSAR estimate for phenol amines class, ECHA data
LC50 - Fish [2]	2.092 mg/l QSAR estimate for aliphatic amines class, ECHA data
LC50 - Other aquatic organisms [2]	0.335 mg/l (daphnia) QSAR estimate for aliphatic amines class, ECHA data
ErC50 algae	0.644 mg/l QSAR estimate for phenol amines class, ECHA data

12.2. Persistence and degradability

Dymalink® 634

Safety Data Sheet

Zinc dimethacrylate (13189-00-9)	
Persistence and degradability	Readily biodegradable.
Biodegradation	92 % (OECD 301F method)

12.3. Bioaccumulative potential

Zinc dimethacrylate (13189-00-9)	
Partition coefficient n-octanol/water (Log Pow)	1.03

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

Section 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Transfer to a safe disposal area in accordance with federal, state, and local regulations.
Product/Packaging disposal recommendations : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Section 14: Transport information

US Transport (DOT) for Bulk Shipments (Non-Bulk Shipments May Differ)

Not regulated by US DOT

Transport by sea (IMDG)

- Transport document description (IMDG) : UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (ZINC SALTS), 9, III, MARINE POLLUTANT
UN Number : UN3077
Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Primary Hazard Class : 9 - Miscellaneous dangerous substances and articles
Packing Group : PGIII
Hazard labels (IMDG) :



- EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG) : A

Air transport (IATA)

- Transport document description (IATA) : UN 3077 Environmentally hazardous substance, solid, n.o.s. (ZINC SALTS), 9, III
UN Number : UN3077
Proper Shipping Name : Environmentally hazardous substance, solid, n.o.s.
Primary Hazard Class : 9 - Miscellaneous Dangerous Substances and Articles
Packing Group : PGIII
Hazard labels (IATA) :



Section 15: Regulatory information

15.1. US Federal regulations

EPA TSCA Status

All components of this product are listed or exempt from listing on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) Active inventory. This product has no special requirements under TSCA, such as significant new use rules (SNUR), consent orders, test rules, or sections 4, 5, 6, 8(a), 8(d), 12(b) requirements.

Dymalink® 634

Safety Data Sheet

SARA Section 313 Supplier Notification

This product contains the following toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372:

CAS number	Chemical name	Concentration
13189-00-9	Zinc dimethacrylate	80 - 100%
Chemical names, CAS numbers, and/or exact concentrations of some components have been withheld as a trade secret		

This product contains one or more zinc compounds. Zinc compounds are listed as a category under SARA 313 and include any unique chemical substance that contains zinc as part of that chemical's infrastructure. See 40 CFR 372.65(c).

This information must be included in all Safety Data Sheets that are copied and distributed for this product. For additional information, see 40 CFR §372.45 Notification About Toxic Chemicals.

SARA Section 311/312 Hazard Classes

Health hazard - Acute toxicity (any route of exposure)
Physical hazard - Combustible dust
Health hazard - Serious eye damage or eye irritation
Health hazard - Respiratory or skin sensitization

Export Control Classification Number (ECCN): EAR99 (No License Required)

15.2. International regulations

CANADA

No additional information available

National inventories

AICS (Australian Inventory of Chemical Substances)	All components are listed or exempted
DSL (Canadian Domestic Substances List)	All components are listed or exempted
IECSC (China Inventory of Existing Chemical Substances)	All components are listed or exempted
EINECS (European Inventory of Existing Commercial Chemical Substances)	All components are listed or exempted
ENCS (Japanese Existing & New Chemical Substances inventory)	All components are listed or exempted
ECL (Korean Existing Chemical List)	All components are listed or exempted
NZIoC (New Zealand Inventory of Chemicals)	Some components are not listed
PICCS (Philippines Inventory of Chemicals and Chemical Substances)	All components are listed or exempted

15.3. US State regulations

California Proposition 65 - To the best of our knowledge, there are no Proposition 65 chemicals present in this product at levels that would require warning under the California Safe Drinking Water and Toxic Enforcement Act.


Section 16: Other information

Other information : This material contains an inhibitor (HQ, MEHQ, etc.) at < 0.1%. The type and amount meet product specifications. Contact a company representative for exact concentrations and details on inhibitor level maintenance.

Unless agreed to in a separate written agreement with the Customer, Resin Solutions, LLC makes no representations and disclaims all warranties, express or implied, with respect to biocompatibility and/or the suitability of this product for medical device applications including : (i) implantable devices intended for human or animal body, (ii) devices intended to be used in contact with internal body fluids, and (iii) devices intended to be used in contact with internal body tissues. If the Customer intends to use this product for any such application, it must first contact Resin Solutions, LLC and establish agreed terms and conditions for such use.

NFPA (National Fire Protection Association)

NFPA health hazard : 3
NFPA fire hazard : 3
NFPA reactivity : 1



Dymalink® 634

Safety Data Sheet

Hazard System Rating

Health	: 3
Flammability	: 3
Physical Hazard	: 1
Personal protection	: See section 8 of SDS

US OSHA LABEL as specified under 29 CFR §1910.1200 (f). The label shown may include supplemental information in addition to required elements.

Dymalink® 634

Resin Solutions, LLC
665 Stockton Drive, Suite 100
Exton, PA 19341 USA
Tel. +1-484-284-8989



Danger

Harmful if swallowed

May cause an allergic skin reaction

Causes serious eye damage

May form combustible dust concentrations in air

Avoid breathing dust.

Wash hands, forearms and face thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear face protection, eye protection, protective gloves.

If swallowed: Call doctor, a POISON CENTER if you feel unwell.

If on skin: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call doctor.

Specific treatment (see Section 4.1 of SDS or information on this label).

Rinse mouth.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

US SDS Version: 3.1

Issue date: November 10, 2023

SDS ID: DYMALINK_634

SDS REFERENCE NUMBER: FP00065

SDS Template - Resin Solutions LLC US Version 1.0

The information contained in this Safety Data Sheet (SDS) is believed by Resin Solutions, LLC to be accurate on the date issued. However, materials may present unknown hazards and should be used with caution. Final determination of suitability and use of any material is the sole responsibility of the user. Neither Resin Solutions, LLC nor any of its subsidiaries or affiliated companies assumes any liability whatsoever for the accuracy or completeness of the information contained herein or reliance thereto. If the material is repackaged, the user is responsible and must ensure that proper health, safety and other necessary information is included with the material and/or on the container. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING THE MATERIALS OR THE INFORMATION CONTAINED IN THIS SDS. ALTERATION OF THIS DOCUMENT IS STRICTLY PROHIBITED.